

Impact Driver LXT® DTD153

18V • 1/4" • 170 Nm • 0 − 3 400 min⁻¹

Extra-compact brushless impact driver for quick driving

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 170 Nm, suitable for quick driving. A handy LED light for added lighting.





Technical specifications

Nominal Battery Voltage Voltage LXT Battery Chemistry (Ni-Cd / Ni-MH / Li- ion)	18 V √ Li-ion
Brushless Motor No load speed	√ 0 - 3400 min ⁻¹
Max Fastening Torque Impact Drill Impacts per Minute (IPM)	170 Nm 0 - 3600 min
Tightening Capacity Standard Bolt Driving Shank Sound Power Level (L _{WA})	M5 - M16 1/4 " 107 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)

3 dB(A)

13,0 m/s²

User benefits

- Low power consumption thanks to brushless motor
- The rubber coating on the handle ensures a firm working grip
- A high impact torque is achieved with the impact screwdriver.
- The screw tip is securely held in place by a quick lateral stroke
- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Quick mount for 1/4 "screwdriver

Link to product - www.makitauk.com

Noise Uncertainty (K Factor)

Vibration Level, Impact Tightening of

Fasteners of the Maximum Capacity of



the Tool

Related products

Optional AC

194250-8

Adaptor Chuck - 1/4 Hex Keyless



821550-0

Makpac case (2)



837670-0

MakPac (2) Inlay



Other

User manual

Parts drawing