

PRODUCT SUMMARY

Valspar® Classic Kitchen & Bathroom is wipeable and resistant to mould & moisture damage. With great coverage in true HD colour, the water-based formula is quick drying and low spatter, making it easy to use and low mess on your walls and ceilings. Resistant to household stains and kitchen grease, Valspar Classic endures the scruffs and knocks of daily life without compromising your colour or finish. Any colour, no compromise, with Valspar.

PRODUCT FEATURES & BENEFITS

- Durable and washable
- Grease and stain resistant
- Mould and moisture resistant

RECOMMENDED USES/SUBSTRATES

- Kitchen
- Bathroom

APPLICATION

- Stir paint thoroughly.
- Mix containers of the same colour for uniformity.
- Stop at a corner or natural break if running out of paint.
- Apply 2 coats using a suitable brush, roller, or sprayer.
- Avoid excessive rolling or brushing.
- Apply liberally, working from dry areas into the wet edge.
- Extra coats may be needed for dramatic colour changes.
- When you dilute the paint, you dilute the quality.
- Dries to touch in approximately 1 hour.
- Wait 2-4 hours before applying the next coat.
- Allow 28 days to cure for ultimate durability.

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.
Protect from freezing.
Packaging: Case of 1

SHERWIN-WILLIAMS.

SURFACE PREPARATION

Read health and safety information before painting.

- For indoor use only
- Do not apply in damp or humid conditions.
- Remove grease, mould and dust completely for a clean & dry surface
- Sand the surface before painting.
- For previously painted surfaces, wash, sand thoroughly, and remove loose or flaky paint
- Fill cracks, dents, or holes with a suitable filler.
- Use a suitable primer when making bold colour changes or when painting difficult surfaces

STORAGE & DISPOSAL

- Remove as much product from application equipment before cleaning.
- Do not wash paint down the drain when washing brushes and rollers.
- Clean painting tools with warm, soapy water.
- Wipe up spills immediately with a damp cloth.
- Please dispose of unused paint responsibly.
- Check with your local authority to see if they provide facilities for the disposal of waste paint.
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses.
- Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish.
- Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product for the protection of the dry paint film from mould growth: IPBC. Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 2-methylisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. VOC content: EU limit for this product (Category A/a): 30 g/l (2010). This product contains a maximum VOC content of 1 g/l.

Please contact Valspar Customer Service on for the safety datasheet, available on request.

PRODUCT SPECIFICATION

Product type:

Acrylic water-based paint

Viscosity:

90 – 110 KU

Sheen:

10 - 20 (60°)

VOC (g/l):

Minimal

Volume solids (before colourant added):

Base A	30% - 31%
--------	-----------

Base B	28% - 29%
--------	-----------

Base C	24% - 25%
--------	-----------

Coverage:

10m²/L

Touch dry:

1 hour

Recoat:

2 – 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C

Storage temperature

Avoid extreme temperatures – do not freeze

Time to cure:

28 days

Test methods:

Our R&D laboratory performs tests following the ISO test methods.

