



## Using the Breaker

1. Wear protective equipment including ear defenders and goggles.
2. The breaker should not be switched on until the tool is on the work surface. It should not be switched on if the tool has no load.
3. Keep the cable clear of the tool bit and any sharp edges on the work.
4. Watch out for signs that vibration may be affecting the hands. If fingers start to tingle or feel numb operators should take a short break from using the machine. Fingers should be exercised to encourage blood flow.
5. To help prevent vibration affecting the hands, the machine should be operated for shorter periods. Hands should be kept warm – wearing gloves may help to do this.
6. If operators think the cable may be cut or damaged in any way, the machine must be switched off and unplugged before inspecting it.
7. Care should be taken not to accidentally pull the plug from the socket.
8. Switch off and remove the plug from the socket before leaving the breaker unattended.
9. If the equipment does not work properly do not attempt to repair it. Contact the hire company.

Please keep this leaflet safely as it may be required for reference at a future date



**Hae**  
HIRE ASSOCIATION EUROPE

Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Soliuhull B37 7YE

Telephone: 44 (0) 121 380 4600  
Fax: 44 (0) 121 333 4109  
Email: [mail@hae.org.uk](mailto:mail@hae.org.uk)  
website: [www.hae.org.uk](http://www.hae.org.uk)

### It is important to read all of this leaflet

#### BEFORE you use the Breaker

1. Electricity is dangerous and must always be used with great care.
2. This heavy duty breaker is designed for breaking up roadwork, concrete and asphalt surfaces; and compacting, using the appropriate tools.
3. The action of this breaker can cause injury or damage if the machine is not used in a careful and controlled way.
4. If operators have not used a breaker before, they should familiarize themselves with the machine on some straightforward work before starting on the main task.
5. The work should be planned ahead and thought out to make sure that it will be carried out safely.
6. The following items of personal protective equipment must be worn as a minimum:  
Impact resistant goggles  
Dust mask  
Ear muffs  
Safety boots  
Gloves
7. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
8. This breaker is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

©Copyright Hire Association Europe April 2011

Telephone: 44 (0) 121 380 4600  
Fax: 44 (0) 121 333 4109  
Email: [mail@hae.org.uk](mailto:mail@hae.org.uk)  
website: [www.hae.org.uk](http://www.hae.org.uk)

Hire Association Europe  
2450 Regents Court  
The Crescent  
Birmingham Business Park  
Soliuhull B37 7YE

**Hae**  
HIRE ASSOCIATION EUROPE

1. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever this machine is used. Particular jobs or environments may require a higher level of protection.  
2. Impact resistant goggles must be worn when using this machine.  
3. This equipment is likely to cause noise levels up to 102 dB(A) – appropriate ear muffs or plugs giving protection up to this level must be worn as a minimum.  
4. An appropriate dust mask is required when breaking material that causes dust.  
5. Safety boots must be worn  
6. Anybody working nearby will also need to wear personal protective equipment.
1. Check the machine, cables, plugs and tool bits. If anything is found to be damaged, do not use the breaker – contact the hire company.  
2. Check that the plug on the machine matches the available supply. Connections must not be forced or improvised.  
3. Machines with a cylindrical yellow industrial plug fitted are designed to run off a special 110V supply. The hire company will have provided a portable transformer if the machine needs to be powered from a normal mains 230V supply. If a portable transformer has been supplied, care must be taken when moving it as it may be heavier than it looks and could cause injury. Machines designed to run directly from 230V mains will have either a normal square pin plug fitted, or a blue industrial plug. Operators should check how the on/off switch operates – before switching the breaker on it must be known how to stop it.
1. Switch the breaker off, and unplug it before changing the tool bit.  
2. The tool shank should be clean and lightly oiled before insertion into the breaker.  
3. Only the correct tool bits specifically for this breaker must be used. No other tool bits should be used.
1. If using a portable transformer, plug the transformer directly into the 230V socket. Do not use any 230V extension cables.  
2. If an extension cable is needed, follow any special instructions given by the hire company. If only a suitably rated heavy duty 110V extension cable should be used, not longer than 50 metres (160 feet). The extension cable must only be used between the transformer and the machine.
1. Use a residual current device ("rcd") plugged directly in to the 230V socket. Plug the machine into the rcd. This will help to protect against electric shock if the cable or machine get damaged.  
2. Use the "TEST" button to check that the rcd is working each time the machine is used. Reset the rcd according to the instructions supplied with it.  
3. If an extension cable is needed, only a suitable rated heavy duty cable should be used, not longer than 50 metres (160 feet). Plug it directly into the rcd.  
4. The extension cable should be laid out carefully, avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It should be fully unrolled or it will overheat and could catch fire.  
5. Extension cable connections must be kept dry and safe.



1. Do not use this breaker where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
2. Make sure that the area is clear and safe and that no-one is nearby who could cause a distraction.
3. Protect other people from the noise, debris and dust. Warn others to keep away, put barriers around the work area.
4. Check that there are no buried electric cables, gas or water pipes where the work is being carried out.
5. Breaking brick and masonry makes a large amount of dust and debris, cover any surfaces or objects that may be damaged, or difficult to clean.

## Before Starting Work...



### WORK AREA

