Page Size: A5

EN Primed wall panelling -Shaker


23/07/24

XX/XX/24

XX/XX/24

19/07/24


16/08/24



1.2 m MDF strips (63 mm x 9 mm) x6

NOTE: Contents of 1 pack covers approximately 1.2 sgm. You will need to add multiple packs together if you require to cover a larger area.

EN You will need



EN Safety

Before you start

- The surface should be free of all dust and debris and loose material
- . To prepare the wall surface, remove any flaking plaster or peeling paint with a scraper or medium-grit sandpaper. Use a cloth to remove any dust or debris.
- . Contents of 1 pack covers approximately 1.2 sqm. You will need to add multiple packs together if you require to cover a larger area.

Safety

• When preparing your walls and installing the wall panelling, you should keep the room you are working in as ventilated as possible. Wear an appropriate mask when sanding and wear safety goggles for eye protection when using machine tools.

Guarantee

We take special care to select high quality materials and use manufacturing techniques that allow us to create products incorporating design and durability. This product has a manufacturer's guarantee of 2 years against manufacturing defects, from the date of purchase (if bought in store) or date of delivery (if bought online), at no additional cost for normal (non-professional or commercial) household use.

To make a claim under this guarantee, you must present your proof of purchase (such as a sales receipt, purchase invoice or other evidence admissible under applicable law), please keep your proof of purchase in a safe place. For this guarantee to apply, the product you purchased must be new, it will not apply to second hand or display products. Unless stated otherwise by applicable law, any replacement product issued under this guarantee will only be guaranteed until expiry of the original period guarantee period.

This guarantee covers product failures and malfunctions provided the product was used for the purpose for which it is intended and subject to installation, cleaning, care and maintenance in accordance with the information contained in these terms and conditions, in the user manual

and standard practice, provided that standard practice does not conflict with the user manual.

This guarantee does not cover defects and damage caused by normal wear and tear or damage that could be the result of improper use, faulty installation or assembly, neglect, accident, misuse, or modification of the product. Unless stated otherwise by applicable law, this guarantee will not cover, in any case, ancillary costs (shipping, movement, costs of uninstalling and reinstalling, labour etc), or direct and indirect damage.

If the product is defective, we will, within a reasonable time, replace.

Rights under this guarantee are enforceable in the country in which you purchased this product. Guarantee related queries should be addressed to the store you purchased this product from.

The guarantee is in addition to and does not affect your statutory rights.

IMPORTANT -**RETAIN THIS INFORMATION** FOR FUTURE **REFERENCE**: **READ CAREFULLY**

Manufacturer:

UK Manufacturer:

Kingfisher International Products Limited, 1 Paddington Square, London, W2 1GG, United Kinadom

EU Manufacturer:

Kingfisher International Products B.V., Rapenburgerstraat 175E, 1011 VM Amsterdam, The Netherlands


EN www.diy.com / www.screwfix.com / www.screwfix.ie To view instruction manuals online. visit www.kingfisher.com/products

EN IMPORTANT - These instructions are for your safety. Please read through them thoroughly prior to handling the product and retain them for future reference.


5063022565051 5063022568557

V10724_5063022565051_MAND2_2324

EN Assembly



EN Measure the wall length to be panelled. Depending on the measurement, cut one or more strips to length to make up horizontal strip across the top of skirting. Apply adhesive in accordance with manufacturer's instructions and press strip(s) to the wall.




02

- EN Calculate the distance between vertical strips using the method described below (it can be used for any wall length).
 - 1. Subtract the width of a single strip from wall length. i.e. for 1800mm wall length subtract strip width 63 mm: 1800 - 63 = 1737 mm
 - 2. Divide the result by desired number of panels (recessed areas between 2 strips).
 - i.e. for 3 panels 1737 mm / 3 = 579 mm
 - 3. Finally, for the distance between vertical strips subtract the width of a single strip. 579 - 63 = 516 mm

Mark it up as shown for next steps.

03




EN For a recessed square panel effect, copy the distance calculated in previous step for horizontal panel strips.

Measure and mark up as shown, depending

i.e. if 2 panels up, mark up the calculated






- EN The length calculated in Step 02 (516 mm in the example) is the length vertical strips need to be cut to.
 - Apply adhesive on cut to length vertical strip and press to the wall.

Repeat steps for all vertical strips to create recessed square panelling effect as shown.

06



EN Fill any gaps and joints with decorator's caulk. Wipe off any excess and sand for a smooth finish if required.

You are now ready to paint.

on how many panels up.

(516 mm) distance between horizontal strips twice as shown.

Length of horizontal strips

EN Cut one or more strips to measured length to make up remaining horizontal strips.

Check with spirit level, apply adhesive and

The horizontal strips can be now used as

press strip(s) to the wall.

guide for vertical strips.