

Before Starting Work.

AAHA XHOW

- ire risk from combustible materials, or Do not use this equipment where there is a
- have adequate ventilation to disperse the or in contined spaces make sure that you If you plan to use the tool for long periods, **'**Z flammable liquids and gases.
- aistract you. Only essential people should ite and that no-one is near to you or could Make sure that your work area is clear and 3 semut tenense
- I his tool should only be used for wood to °t peing used. work in the area when the cordless nailer is
- Only use nails recommended by the hire **.** ک .pood nailing.
- Protect other people from the holse and .9 company in this tool.
- ole, put barriers around your w danger. Warn others to keep away. If
- where there is excessive moisture. Do not use the cordless nailer in the rain or 'R9'R

SROTAR390

Speedy

- nuderstanding of the equipment and the if you have adequate knowledge and You should only operate this cordless nailer
- equipment (PPE) are the minimum that The following items of personal protective <u>ح</u>. ourself or others. job to enable you to use it without risk to
- protection. environments may require a higher level of should be worn whenever you use the
- up to 98 dBh wear appropriate ear mutte This cordiess nailer will cause noise levels 3
- Impact resistant goggles, or face shield .4 .muminim s ss ieve or plugs giving nearing protection for this
- when working with this equipment.
- Strong gloves will help protect your hands. ·G

ibility for any loss or liability perc

- มกอา ระบอดอา กระ vesociation ⊨urope

- :lism3

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

- **3YT TEB Iludilos** The Crescent Birmingham Business Park :euoudeie

aterial. Only Acts of Parliament and S



.7

.9

'G

·t

31

'Z

-9

·uoisoidxa

siut


neat.

patteries,

CORDLESS NAILER

horecrive equipment.

to have arisen from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.



is accurate and not misleading. HAE/EHA cannot accept respo

2208 Safety Guidance

Read this entire leaflet before using the Paslode IM65

carefully and only by trained operators.

area. Never allow a child to touch the equipment.

remove them when the equipment is not in use.

not to cause a fire or explosion.

This equipment can be hazardous if misused. It should be used

The fuel in the cells is highly flammable: any source of ignition

including a lighted cigarette, could be hazardous. Take great care

Keep non-essential people, especially children away from the work

Do not insert a fuel cell, battery, or fasteners until required, and

Keep the equipment safely in its protective case when it is not in use.

or permanent disability must seek expert advice before using it.

Paslode IM65

The rules and procedures in force where people are at work

may require the person responsible for this equipment

to carry out a specific risk assessment

Always keep the nailer pointing away from yourself, and others. Keep your fingers away from the

Do not allow the work-contact element to be accidentally depressed against your body or any

Do not indulge in any horseplay or irresponsible behaviour, while using, or working near the

This cordless nailer must not be used by minors, or by anyone under the influence of drugs or

This equipment is designed for operation by an able bodied adult. Anyone with either temporary

You should wear the following items of personal protective equipment: ear muffs or plugs giving

protection for levels up to 98 dBA; impact resistant goggles or face shield and strong work

You may also need a residual current device (rcd) if charging batteries from a 230-volt mains




44 (0) 121 380 4600









battery from the cordless nailer before

You must always unload the fuel cell and

Do not point the cordless nailer at anyone,

immediate use. It should remain unloaded,

into the cordless nailer until it is required for

Do not load a fuel cell, battery, or fasteners

cordless nailer could cause

explosive gas. Any source of ignition including a lighted cigarette or the firing of

would rapidly evaporate into a large area of

It their escapes from a punctured cell, it

ireproof box, away from any source of

Fuel cells must be stored in a secure

anything found damaged - contact the hire

Check your cordless nailer, fuel cells,

Anybody who is working near to you will

and tasteners. Do not use

of to wear appropriate person

in its storage box, when not in use.

even when it is not loaded.

onto a tire. ių aut

understand how to use the cordless nailer Before you start work, make sure you

sately with no danger to yourself or others.



1.

7.

8

9.

10

11.

trigger

aloves 12.

supply

other object.

cordless nailer.

'G

3

.s

1

·•

3

·7

1

10 1030.

company.

penetration.

LOADING FUEL CELLS

adjustment is made.

tterent lengths.

TNAMTSULGA HT940

tart using the equipment.

towards the back of the handle.

cover inwards then swinging it down

The fuel cell compartment is located at the back of the nailer. Open it by pressing the

the cell until it clicks twice. It is now ready

down, and then push the back down onto

Push the front of the valve forwards and

cell with the front pointing away from you.

rake the cap off the valve by pulling it back

remove the valve and cap from the cell, and

cell until a hiss of gas is released. Then

First, push the valve and cap onto the fuel

You need to fit the metering valve to the tuel

have been supplied or specified by the hire

Use only tuel cells and metering valves that

Reload the battery when you are ready to

Turn the adjustment wheel near the nose of

The battery must be removed before any

deptus of penetration, and for fasteners of

Its position can be adjusted to for different

tool that is pushed against the work piece

The work-contact element is the part of the

machine to adjust the depth of

cell before you can load the cell.

Put the valve back in position on the fuel

44 (0) 121 380 4600 44 (0) 121 333 4109

e.org.uk

USING THE CORDLESS NAILER

goggles and ear defenders.

the fuel cell and battery first.

timber take care not to split it.

1. Wear your protective equipment including

Do not carry a loaded nailer around: unload

To fix a nail, press the work-contact element

against the workpiece, and pull the trigger.

This equipment will drive two to three nails

per second, or up to 500 per hour. Do not

try to force it to work faster - it will damage

When working close to the edge of your

When you have finished work, unload and

clean the cordless nailer and store it and

the fuel cells, battery and fasteners

If your equipment is not working properly or

repair it. Contact the hire company.

appears to be faulty, do not attempt to

Any unsuffortised reproduction – manually or electronically – is STHICILY prohibited

©Copyright Hire Association Europe April 2011

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

2.

3

5.

6.

7.

Please keep this leaflet safely. It may be required for further information

the tool.

securely

LOADING NAILS

1.

4

5.

8.

Use only nails or other fasteners that have

been supplied or specified by the hire

company. If you need different nails,

Do not operate the trigger, or have the yoke

Holding the tool by its handle in your right

hand, align the heads of the nails with the

silver channel in the rear of the magazine

Squeeze the release level and pull the

follower ring to the rear of the magazine

until the follower passes the last of the

Release the follower and let it push the

As the fasteners are used, the strip will be

pushed along. The indicator at the side of

the magazine will show when the tool

When there are approximately 10fasteners left a safety mechanism will prevent further

operation. Reload a fresh strip of fasteners

nails forward into the nose of the tool.

depressed while loading or unloading.

contact the hire company

and insert one or two strips.

Push the nail strips forward.

requires reloading.

.01

.6

.8

-2

-9

·g

3

·7

. pəsn

YAHTTAB

landpop

gham Business Park

Hire Association Europe

2450 Regents Court

olibull B37 7YE

The Crescent

αλ τυς μις company.

recharging.

rue parrery.

rue parrery.

condition of the battery.

by the hire company.

cell does not move.

- cool, well-ventilated and sate location.
- Charging should be carried out in a dry,
- when charging some types of batteries.

If you have an rcd, plug it into the 230- volt

supplied, following the instructions give

Recharge the battery only with the charger

A continuous red light shows that the

depressed, a continuous green light show

red, the battery is flat: you should recharge

depressed, a flashing green light shows that the battery is in tool. If the light flashes

When the work-contact element is not

display either red or green to indicate the

The light emitting diode in the handle will

equipment upside down to insert or remove

The battery compartment is located on the right side of the magazine. Hold the

edulpment as supplied or recommended

Use only the correct batteries for your

Remove the battery if the tool is not being

inserted even it the tool is not being used.

The battery will slowly discharge while

Shut the compartment, making sure the fuel

valve into the Yellow aperture in the

6. Load the fuel cell in so that the metering valve goes in last. Locate the stem of the

When the work-contact element

101

SI

The battery must be removed

battery is flat and needs recharging.

that battery is charged ready for use.

11. Toxic and flammable fumes are produced

socket. Plug the charger into the rcd.